



SAFETY DATA SHEET

XIAMETER PMX 200 SILICONE FLUID 300 CST

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	XIAMETER PMX 200 SILICONE FLUID 300 CST
Product number	56900
REACH registration notes	Exempt -polymer exempt by Article 2(9) This product is not classified as hazardous, the information in this datasheet is given for guidance only.
CAS number	63148-62-9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Lubricant. Lubricant. Additive
-----------------	-----------------------------------

1.3. Details of the supplier of the safety data sheet

Supplier	Univar Solutions UK Ltd Aquarius House 6 Mid Point Business Park Bradford BD3 7AY +44 1274 267300 +44 1274 267306 SDS.EMEA@univarsolutions.com
----------	---

1.4. Emergency telephone number

Emergency telephone	SGS - +32 (0)3 575 55 55 (24h)
Sds No.	56900

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Not Classified
Environmental hazards	Not Classified

2.2. Label elements

Hazard statements	NC Not Classified
-------------------	-------------------

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria. The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

XIAMETER PMX 200 SILICONE FLUID 300 CST

3.1. Substances

POLYDIMETHYLSILOXANE CAS number: 63148-62-9 Polymer	<=100.0%
Classification Not Classified	

The full text for all hazard statements is displayed in Section 16.

Product name	XIAMETER PMX 200 SILICONE FLUID 300 CST
REACH registration notes	Exempt -polymer exempt by Article 2(9) This product is not classified as hazardous, the information in this datasheet is given for guidance only.
CAS number	63148-62-9
Composition comments	The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Wear protective clothing as described in Section 8 of this safety data sheet.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	May cause temporary eye irritation.
--------------------	-------------------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	When heated and in case of fire, toxic vapours/gases may be formed.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Formaldehyde Oxides of the following substances: Silicon. Carbon.

5.3. Advice for firefighters

XIAMETER PMX 200 SILICONE FLUID 300 CST

Protective actions during firefighting	No action shall be taken without appropriate training or involving any personal risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Do not use water jet as an extinguisher, as this will spread the fire. Contain and collect extinguishing water. Control run-off water by containing and keeping it out of sewers and watercourses. Evacuate area.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Stop leak if safe to do so. Absorb spillage with inert, damp, non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Avoid the spillage or runoff entering drains, sewers or watercourses.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in Section 13.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Avoid spilling. Avoid release to the environment. Observe good chemical hygiene practices. Product residues retained in emptied containers can be hazardous.
--------------------------	--

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place. Only store in correctly labelled containers. Store away from the following materials: Strong oxidising agents.
----------------------------	--

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Ingredient comments	No exposure limits known for ingredient(s).
----------------------------	---

POLYDIMETHYLSILOXANE (CAS: 63148-62-9)

Ingredient comments	No exposure limits known for ingredient(s).
----------------------------	---

XIAMETER PMX 200 SILICONE FLUID 300 CST

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The selected gloves should have a breakthrough time of at least 1 hours. Butyl rubber. Rubber (natural, latex). Neoprene. Nitrile rubber. Polyvinyl chloride (PVC). Thickness: > 0.35 mm To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Remove contaminated clothing and protective equipment before entering eating areas. Eye wash facilities and emergency shower must be available when handling this product.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. If ventilation is inadequate, suitable respiratory protection must be worn. Organic vapour filter. Combination filter, type A2/P2. EN 136/140/141/145/143/149

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	Characteristic.
Odour threshold	No information available.
pH	No information available.
Melting point	No information available.
Pour Point	No information available.
Freezing Point	Not determined.
Initial boiling point and range	>=65°C @ 760 mm Hg
Flash point	> 101°C Closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.

XIAMETER PMX 200 SILICONE FLUID 300 CST

Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	No information available.
Other flammability	No information available.
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	0.97
Bulk density	No information available.
Solubility(ies)	Not determined.
Partition coefficient	Not determined.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	300 cSt @ 25°C
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	No information available.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information	No information available.
Refractive index	No information available.
Particle size	Not applicable.
Molecular weight	No information available.
Volatility	No information available.
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	The following materials may react with the product: Strong oxidising agents. Will decompose at temperatures exceeding 150°C. When heated, vapours/gases hazardous to health may be formed. Formaldehyde Provide adequate ventilation.
---	---

10.4. Conditions to avoid

Conditions to avoid	None known.
----------------------------	-------------

XIAMETER PMX 200 SILICONE FLUID 300 CST

10.5. Incompatible materials

Materials to avoid Avoid contact with strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Formaldehyde Oxides of the following substances: Silicon. Carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) This product has low toxicity. This information is based on test data from similar products LD₅₀ > 48500 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) This information is based on test data from similar products LD₅₀ > 2000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined.

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation May cause temporary eye irritation.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation Not sensitising. Guinea pig

Germ cell mutagenicity

Genotoxicity - in vitro This information is based on test data from similar products This substance has no evidence of mutagenic properties. Negative.

Carcinogenicity

Carcinogenicity This information is based on test data from similar products No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Reproductive toxicity - fertility This information is based on test data from similar products No evidence of reproductive toxicity in animal studies.

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met. Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

XIAMETER PMX 200 SILICONE FLUID 300 CST

Toxicokinetics	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system.
Ingestion	This product has low toxicity. No harmful effects expected from quantities likely to be ingested by accident. May cause discomfort if swallowed.
Skin contact	Skin irritation should not occur when used as recommended.
Eye contact	May cause temporary eye irritation.

SECTION 12: Ecological information

Ecotoxicity	The product is not expected to be hazardous to the environment. However, large or frequent spills may have hazardous effects on the environment.
--------------------	--

12.1. Toxicity

Toxicity	There are no data on the ecotoxicity of this product.
-----------------	---

Acute aquatic toxicity

Acute toxicity - aquatic invertebrates	This information is based on test data from similar products EC ₅₀ , 48 hours: > 200 mg/l, Daphnia magna
---	--

12.2. Persistence and degradability

Persistence and degradability	There are no data on the degradability of this product.
--------------------------------------	---

12.3. Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
----------------------------------	---------------------------------------

Partition coefficient	Not determined.
------------------------------	-----------------

12.4. Mobility in soil

Mobility	No information available.
-----------------	---------------------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

12.6. Other adverse effects

Other adverse effects	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------------------------	---

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste should be treated as controlled waste. Do not puncture or incinerate, even when empty. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
----------------	--

XIAMETER PMX 200 SILICONE FLUID 300 CST

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

COMMISSION REGULATION (EU) 2020/878 of 18 June 2020

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

US - TSCA

All the ingredients are listed or exempt.

Australia - AICS

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

SECTION 16: Other information

XIAMETER PMX 200 SILICONE FLUID 300 CST

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
 CAS: Chemical Abstracts Service.
 DNEL: Derived No Effect Level.
 IATA: International Air Transport Association.
 IMDG: International Maritime Dangerous Goods.
 Kow: Octanol-water partition coefficient.
 LC₅₀: Lethal Concentration to 50 % of a test population.
 LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
 PBT: Persistent, Bioaccumulative and Toxic substance.
 PNEC: Predicted No Effect Concentration.
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
 RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
 vPvB: Very Persistent and Very Bioaccumulative.
 IARC: International Agency for Research on Cancer.
 MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.
 cATpE: Converted Acute Toxicity Point Estimate.
 BCF: Bioconcentration Factor.
 BOD: Biochemical Oxygen Demand.
 EC₅₀: 50% of maximal Effective Concentration.
 LOAEC: Lowest Observed Adverse Effect Concentration.
 LOAEL: Lowest Observed Adverse Effect Level.
 NOAEC: No Observed Adverse Effect Concentration.
 NOAEL: No Observed Adverse Effect Level.
 NOEC: No Observed Effect Concentration.
 LOEC: Lowest Observed Effect Concentration.
 DMEL: Derived Minimal Effect Level.
 EL50: Exposure Limit 50
 hPa: Hectopascal
 LL50: Lethal Loading fifty
 OECD: Organisation for Economic Co-operation and Development
 POW: Octanol-water partition coefficient
 SCBA: self-contained breathing apparatus
 STP: Sewage Treatment Plant
 VOC: Volatile Organic Compounds

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity
 Aquatic Acute = Hazardous to the aquatic environment (acute)
 Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Key literature references and sources for data

Supplier's information.

Revision comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date

17/02/2023

Version number

4.000

Supersedes date

05/03/2020

SDS number

56900

XIAMETER PMX 200 SILICONE FLUID 300 CST**SDS status**

Approved.

Signature

Lisa Bland

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.