



SAFETY DATA SHEET ECOSURF LFE-635 SURFACTANT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	ECOSURF LFE-635 SURFACTANT
Product number	58364
REACH registration notes	Exempt -polymer exempt by Article 2(9)
CAS number	64366-70-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Surfactant
-----------------	------------

1.3. Details of the supplier of the safety data sheet

Supplier	Univar Aquarius House 6 Mid Point Business Park Bradford BD3 7AY +44 1274 267300 +44 1274 267306 sds@univar.com
----------	--

1.4. Emergency telephone number

Emergency telephone	SGS - +32 (0)3 575 55 55 (24h)
Sds No.	58364

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Eye Irrit. 2 - H319
Environmental hazards	Not Classified

2.2. Label elements

Hazard pictograms



Signal word	Warning
Hazard statements	H319 Causes serious eye irritation.

ECOSURF LFE-635 SURFACTANT

Precautionary statements	P264 Wash contaminated skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention.
---------------------------------	--

2.3. Other hazards

Take care as floors and other surfaces may become slippery.

SECTION 3: Composition/information on ingredients

3.1. Substances

2-ETHYLHEXANOL ETHOXYATED PROPOXYLATED	> 99.0%
CAS number: 64366-70-7	
Polymer	
Classification	
Eye Irrit. 2 - H319	

The full text for all hazard statements is displayed in Section 16.

Product name	ECOSURF LFE-635 SURFACTANT
REACH registration notes	Exempt -polymer exempt by Article 2(9)
CAS number	64366-70-7
Composition comments	The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	First aid personnel should wear appropriate protective equipment during any rescue. Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting unless under the direction of medical personnel. Rinse mouth thoroughly with water. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	Causes mild skin irritation. Prolonged skin contact may cause redness and irritation.
Eye contact	Causes serious eye irritation. May cause chemical eye burns. Symptoms following overexposure may include the following: Severe irritation, burning and tearing. Corneal damage.

4.3. Indication of any immediate medical attention and special treatment needed

ECOSURF LFE-635 SURFACTANT

Notes for the doctor No specific recommendations. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards When heated, vapours/gases hazardous to health may be formed.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO). Toxic gases or vapours. Irritating gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting No action shall be taken without appropriate training or involving any personal risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Control run-off water by containing and keeping it out of sewers and watercourses. Contain and collect extinguishing water. Evacuate area.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Follow precautions for safe handling described in this safety data sheet. Keep unnecessary and unprotected personnel away from the spillage. Provide adequate ventilation. Avoid inhalation of vapours and contact with skin and eyes. Do not touch or walk into spilled material. Take care as floors and other surfaces may become slippery.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with inert, damp, non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Clean contaminated objects and areas thoroughly, observing environmental regulations.
Do not use the following: Water.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

ECOSURF LFE-635 SURFACTANT

Usage precautions

Handle all packages and containers carefully to minimise spills. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid inhalation of vapours and contact with skin and eyes. Take care as floors and other surfaces may become slippery.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Provide eyewash station and safety shower.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid excessive heat for prolonged periods of time.
Store away from the following materials: Strong oxidising agents. Strong acids. Strong alkalis.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Ingredient comments

No exposure limits known for ingredient(s).

2-ETHYLHEXANOL ETHOXYATED PROPOXYLATED (CAS: 64366-70-7)

Ingredient comments

No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Avoid inhalation of vapours and contact with skin and eyes. Provide eyewash station and safety shower.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material. The selected gloves should have a breakthrough time of at least 2 hours. It is recommended that gloves are made of the following material: Butyl rubber. Rubber (natural, latex). Neoprene. Nitrile rubber. Polyvinyl alcohol (PVA). Polyvinyl chloride (PVC).

Protective gloves should have a minimum thickness of 0.35 mm. Frequent changes are recommended.

ECOSURF LFE-635 SURFACTANT

Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Wash contaminated clothing before reuse.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3. EN 136/140/141/145/143/149

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless. to Yellow.
Odour	Mild.
Odour threshold	No information available.
pH	pH (diluted solution): 5.0 - 7.5 (aqueous solution)
Melting point	~ 5°C
Initial boiling point and range	No information available.
Flash point	263°C Closed cup.
Evaporation rate	No information available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	No information available.
Vapour pressure	< 0.01 mm Hg @ 20°C Estimated value.
Vapour density	> 1 (air =1) Estimated value.
Relative density	1.004 @ 20°C Estimated value.
Solubility(ies)	Soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	44 cSt @ 40°C Estimated value.
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information	Not determined.
--------------------------	-----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

ECOSURF LFE-635 SURFACTANT

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong acids. Strong alkalis. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO). Toxic gases or vapours. Irritating gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.
LD₅₀ > 2000 mg/kg, Oral, Rat, Female Read-across data.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.
LD₅₀ > 2000 mg/kg, Dermal, Rabbit (0 Death.) Read-across data.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. Read-across data.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo No information available.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - fertility No information available.

ECOSURF LFE-635 SURFACTANT

Reproductive toxicity - development No information available.

Specific target organ toxicity - single exposure

STOT - single exposure Inconclusive data. Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system.

Ingestion This product has low toxicity. No harmful effects expected from quantities likely to be ingested by accident. Contact physician if larger quantity has been consumed. May cause internal injury.

Skin contact Causes mild skin irritation. Prolonged skin contact may cause redness and irritation.

Eye contact Causes serious eye irritation. May cause chemical eye burns. Symptoms following overexposure may include the following: Severe irritation, burning and tearing. Corneal damage.

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hour: 32 mg/l, *Oncorhynchus mykiss* (Rainbow trout)
Read-across data.

Acute toxicity - aquatic invertebrates EC₅₀, 48 hour: > 100 mg/l, *Daphnia magna*

Acute toxicity - aquatic plants ErC₅₀, 72 hour: 31.9 mg/l, *Desmodesmus subspicatus*
Read-across data.
NOEC, 72 hour: 6.25 mg/l, Freshwater algae
Raphidoclis subcapitata
Read-across data.

12.2. Persistence and degradability

Persistence and degradability The product is readily biodegradable. Read-across data.

Biodegradation Water - Degradation > 60%: 28 day
Read-across data.

12.3. Bioaccumulative potential

Bioaccumulative potential No specific test data are available.
BCF: 1.56, Fish Estimated value.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No information available.

12.5. Results of PBT and vPvB assessment

ECOSURF LFE-635 SURFACTANT

Results of PBT and vPvB assessment Not determined.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Do not puncture or incinerate, even when empty. Do not discharge into drains or watercourses or onto the ground. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

ECOSURF LFE-635 SURFACTANT

Not applicable.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
 CAS: Chemical Abstracts Service.
 DNEL: Derived No Effect Level.
 IATA: International Air Transport Association.
 IMDG: International Maritime Dangerous Goods.
 Kow: Octanol-water partition coefficient.
 LC₅₀: Lethal Concentration to 50 % of a test population.
 LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
 PBT: Persistent, Bioaccumulative and Toxic substance.
 PNEC: Predicted No Effect Concentration.
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
 RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
 vPvB: Very Persistent and Very Bioaccumulative.
 IARC: International Agency for Research on Cancer.
 MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.
 cATpE: Converted Acute Toxicity Point Estimate.
 BCF: Bioconcentration Factor.
 BOD: Biochemical Oxygen Demand.
 EC₅₀: 50% of maximal Effective Concentration.
 LOAEC: Lowest Observed Adverse Effect Concentration.
 LOAEL: Lowest Observed Adverse Effect Level.
 NOAEC: No Observed Adverse Effect Concentration.
 NOAEL: No Observed Adverse Effect Level.
 NOEC: No Observed Effect Concentration.
 LOEC: Lowest Observed Effect Concentration.
 DMEL: Derived Minimal Effect Level.
 EL50: Exposure Limit 50
 hPa: Hectopascal
 LL50: Lethal Loading fifty
 OECD: Organisation for Economic Co-operation and Development
 POW: Octanol-water partition coefficient
 SCBA: self-contained breathing apparatus
 STP: Sewage Treatment Plant
 VOC: Volatile Organic Compounds

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity
 Aquatic Acute = Hazardous to the aquatic environment (acute)
 Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Key literature references and sources for data

Supplier's information.

Revision date

29/07/2019

Version number

1.000

ECOSURF LFE-635 SURFACTANT

SDS number	58364
SDS status	Approved.
Hazard statements in full	H319 Causes serious eye irritation.
Signature	Jacq Pattinson