



SAFETY DATA SHEET

PRIMAL AC 261K ACRYLIC EMULSION

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PRIMAL AC 261K ACRYLIC EMULSION

Product number 61021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Binder

1.3. Details of the supplier of the safety data sheet

Supplier Univar Solutions UK Ltd
Aquarius House
6 Mid Point Business Park
Bradford
BD3 7AY
+44 1274 267300
+44 1274 267306
SDS.EMEA@univarsolutions.com

1.4. Emergency telephone number

Emergency telephone SGS - +32 (0)3 575 55 55 (24h)

Sds No. 61021

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE, 2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE. May produce an allergic reaction.

Supplemental label information EUH210 Safety data sheet available on request.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PRIMAL AC 261K ACRYLIC EMULSION

1,2-BENZISOTHIAZOL-3(2H)-ONE

>= 0.025 - < 0.05 %

CAS number: 2634-33-5

EC number: 220-120-9

M factor (Acute) = 1

Acute Toxicity Estimate (oral): 675.3 mg/kg

Acute Toxicity Estimate (dermal): > 5,000 mg/kg

Skin Sens. 1 - H317 >= 0.05%

Classification

Acute Tox. 4 - H302

Skin Irrit. 2 - H315

Eye Dam. 1 - H318

Skin Sens. 1 - H317

Aquatic Acute 1 - H400

Aquatic Chronic 3 - H412

DITHIO-2,2 BIS(BENZMETHYLAMIDE)

>= 0.0025 - < 0.025 %

CAS number: 2527-58-4

EC number: 219-768-5

M factor (Acute) = 1

Acute Toxicity Estimate (oral): > 5000 mg/kg

Acute Toxicity Estimate (dermal): > 2000 mg/kg

Classification

Skin Sens. 1 - H317

Aquatic Acute 1 - H400

Aquatic Chronic 2 - H411

2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE

>= 0.0002 - < 0.0015 %

CAS number: 2527-66-4

EC number: 695-989-4

M factor (Acute) = 1

Acute Toxicity Estimate (oral): 175 mg/kg

Acute Toxicity Estimate (dermal): 1100 mg/kg

Acute Toxicity Estimate (inhalation): > 0.5328 mg/l Dust/Mist 4 hours

Skin Sens. 1A - H317 >= 0.0015 %

Classification

Acute Tox. 3 - H301

Acute Tox. 4 - H312

Skin Corr. 1C - H314

Eye Dam. 1 - H318

Skin Sens. 1A - H317

Aquatic Acute 1 - H400

Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

PRIMAL AC 261K ACRYLIC EMULSION

General information	First aid personnel should wear appropriate protective equipment during any rescue. Wear protective clothing as described in Section 8 of this safety data sheet.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Get medical attention if any discomfort continues. Wash clothing and clean shoes thoroughly before reuse. Provide shower facilities near the workplace.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	The product contains a small amount of sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	When heated and in case of fire, toxic vapours/gases may be formed.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of the following substances: Carbon.

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Keep unnecessary and unprotected personnel away from the spillage. Keep upwind. Take care as floors and other surfaces may become slippery.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	--

PRIMAL AC 261K ACRYLIC EMULSION

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if safe to do so. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Wash skin thoroughly after handling. Container must be kept tightly closed when not in use.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid freezing. Stir well before use. Store at temperatures between 1°C and 49°C.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Ingredient comments No exposure limits known for ingredient(s).

1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)

DNEL	Workers - Dermal; Long term systemic effects: 0.966 mg/kg Workers - Inhalation; Long term systemic effects: 6.81 mg/m ³ Consumer - Dermal; Long term systemic effects: 0.345 mg/kg Consumer - Inhalation; Long term systemic effects: 1.2 mg/m ³
PNEC	Fresh water; 0.004 mg/l marine water; 0.0004 mg/l Intermittent release; 0.0011 mg/l STP; 1.03 mg/l Sediment (Freshwater); 0.0499 mg/kg Sediment (Marinewater); 0.00499 mg/kg Soil; 3.0 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

PRIMAL AC 261K ACRYLIC EMULSION

Hand protection	The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The selected gloves should have a breakthrough time of at least 4 hours. Neoprene. Nitrile rubber. Polyvinyl chloride (PVC). Thickness: > 0.35 mm Do not use the following: Polyvinyl alcohol (PVA). To protect hands from chemicals, gloves should comply with European Standard EN374.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures	When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Remove contaminated clothing and protective equipment before entering eating areas. Eye wash facilities and emergency shower must be available when handling this product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. If ventilation is inadequate, suitable respiratory protection must be worn. Organic vapour filter. Combination filter, type A2/P2. EN 136/140/141/145/143/149

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Milky. White.
Odour	Ammonia.
Odour threshold	No information available.
pH	pH (concentrated solution): 8.5 - 9.1
Melting point	0°C Water
Pour Point	No information available.
Freezing Point	No information available.
Initial boiling point and range	100.00°C @ 760 mm Hg Water
Flash point	The product is non-combustible.
Evaporation rate	< 1.00 (butyl acetate = 1) Water
Evaporation factor	No information available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Other flammability	No information available.
Vapour pressure	2266.4808000 Pa @ 20°C Water
Vapour density	< 1.0000 Water
Relative density	1.0000 - 1.2000
Bulk density	No information available.
Solubility(ies)	Partly miscible.

PRIMAL AC 261K ACRYLIC EMULSION

Partition coefficient	No information available.
Auto-ignition temperature	Not applicable.
Decomposition Temperature	No information available.
Viscosity	50.000 - 400.000 mPa.s
Explosive properties	No information available.
Explosive under the influence of a flame	No information available.
Oxidising properties	No information available.

9.2. Other information

Refractive index	No information available.
Particle size	No information available.
Molecular weight	No information available.
Volatility	49.00 - 51.00 % Water
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not polymerise.
------------------------------------	----------------------

10.4. Conditions to avoid

Conditions to avoid	Avoid freezing.
---------------------	-----------------

10.5. Incompatible materials

Materials to avoid	None known.
--------------------	-------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of the following substances: Carbon.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD ₅₀)	This product has low toxicity. This information is based on test data from similar products LD ₅₀ > 5000 mg/kg, Oral, Rat
--------------------------------	--

Acute toxicity - dermal

PRIMAL AC 261K ACRYLIC EMULSION

Notes (dermal LD₅₀)	This information is based on test data from similar products LD ₅₀ > 2000 mg/kg, Dermal, Rabbit
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	Not determined.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	This information is based on test data from similar products May be slightly irritating to skin. Redness.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	This information is based on test data from similar products May cause temporary eye irritation.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	No information available.
<u>Skin sensitisation</u>	
Skin sensitisation	The product contains a small amount of sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	No information available.
<u>Carcinogenicity</u>	
Carcinogenicity	No information available.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No information available.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No information available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	No information available.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
<u>Inhalation</u>	
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system.
<u>Ingestion</u>	
Ingestion	May cause discomfort if swallowed.
<u>Skin contact</u>	
Skin contact	May be slightly irritating to skin. Redness. The product contains a small amount of sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals.
<u>Eye contact</u>	
Eye contact	May cause temporary eye irritation.

Toxicological information on ingredients.

1,2-BENZISOTHIAZOL-3(2H)-ONE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 675.3

Species Rat

Notes (oral LD₅₀) LD₅₀ 675.3 mg/kg, Oral, Rat Harmful if swallowed.

PRIMAL AC 261K ACRYLIC EMULSION

ATE oral (mg/kg) 675.3

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 5000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined.

Skin corrosion/irritation

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye damage. May cause permanent damage if eye is not immediately irrigated. May cause chemical eye burns.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - fertility This substance has no evidence of toxicity to reproduction.

Reproductive toxicity - development This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met. Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Toxicokinetics

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system.

Ingestion Harmful if swallowed.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

PRIMAL AC 261K ACRYLIC EMULSION

Eye contact Causes serious eye damage. May cause permanent damage if eye is not immediately irrigated. May cause chemical eye burns.

DITHIO-2,2 BIS(BENZMETHYLAMIDE)

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 2000 mg/kg, Dermal, Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined.

Skin corrosion/irritation

Skin corrosion/irritation May be slightly irritating to skin. Redness.

Serious eye damage/irritation

Serious eye damage/irritation May be slightly irritating to eyes.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro No information available.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - fertility No information available.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met. Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Toxicokinetics

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system.

Ingestion May cause discomfort if swallowed.

PRIMAL AC 261K ACRYLIC EMULSION

Skin contact	May be slightly irritating to skin. Redness. May cause an allergic skin reaction.
Eye contact	May be slightly irritating to eyes.

2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE

Acute toxicity - oral

Notes (oral LD₅₀)	Toxic if swallowed. LD ₅₀ ATE: 175 mg/kg, Oral, Rat Estimated value.
-------------------------------------	--

ATE oral (mg/kg)	175.0
-------------------------	-------

Acute toxicity - dermal

Notes (dermal LD₅₀)	Harmful in contact with skin. LD ₅₀ ATE: 1100 mg/kg, Dermal, Rabbit Estimated value.
---------------------------------------	--

ATE dermal (mg/kg)	1,100.0
---------------------------	---------

Acute toxicity - inhalation

Notes (inhalation LC₅₀)	LC ₅₀ > 0.5328 mg/l, 4 hours, Dust/Mist Rat
---	--

Skin corrosion/irritation

Skin corrosion/irritation	Causes severe burns.
----------------------------------	----------------------

Serious eye damage/irritation

Serious eye damage/irritation	Causes serious eye damage. May cause permanent damage if eye is not immediately irrigated. May cause chemical eye burns.
--------------------------------------	--

Respiratory sensitisation

Respiratory sensitisation	No information available.
----------------------------------	---------------------------

Skin sensitisation

Skin sensitisation	May cause an allergic skin reaction.
---------------------------	--------------------------------------

Germ cell mutagenicity

Genotoxicity - in vitro	Negative.
--------------------------------	-----------

Carcinogenicity

Carcinogenicity	No information available.
------------------------	---------------------------

Reproductive toxicity

Reproductive toxicity - fertility	No evidence of reproductive toxicity in animal studies.
--	---

Specific target organ toxicity - single exposure

STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
-------------------------------	---

Specific target organ toxicity - repeated exposure

STOT - repeated exposure	No information available.
---------------------------------	---------------------------

Aspiration hazard

Aspiration hazard	Based on available data the classification criteria are not met.
--------------------------	--

PRIMAL AC 261K ACRYLIC EMULSION

Toxicokinetics	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system.
Ingestion	Toxic if swallowed.
Skin contact	Harmful in contact with skin. Causes severe burns. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage. May cause permanent damage if eye is not immediately irrigated. May cause chemical eye burns.

SECTION 12: Ecological information

Ecotoxicity	The product is not expected to be hazardous to the environment. However, large or frequent spills may have hazardous effects on the environment.
--------------------	--

Ecological information on ingredients.

1,2-BENZISOTHIAZOL-3(2H)-ONE

Ecotoxicity	Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.
--------------------	--

DITHIO-2,2 BIS(BENZMETHYLAMIDE)

Ecotoxicity	Very toxic to aquatic life with long lasting effects.
--------------------	---

2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE

Ecotoxicity	Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
--------------------	--

12.1. Toxicity

Toxicity	Not considered toxic to fish.
-----------------	-------------------------------

Ecological information on ingredients.

1,2-BENZISOTHIAZOL-3(2H)-ONE

Toxicity	Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.
-----------------	--

Acute aquatic toxicity

LE(C)₅₀	0.1 < L(E)C ₅₀ ≤ 1
---------------------------	-------------------------------

M factor (Acute)	1
-------------------------	---

Acute toxicity - fish	LC ₅₀ , 96 hours: 1.9 mg/l, Oncorhynchus mykiss (Rainbow trout)
------------------------------	--

Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 3.7 mg/l, Daphnia magna
---	--

Acute toxicity - aquatic plants	ErC ₅₀ , 72 hours: 0.8 mg/l, Pseudokirchneriella subcapitata NOEC, 72 hours: 0.21 mg/l, Pseudokirchneriella subcapitata ErC ₅₀ , 72 hours: 0.36 mg/l, Skeletonema costatum NOEC, 72 hours: 0.15 mg/l, Skeletonema costatum
--	---

PRIMAL AC 261K ACRYLIC EMULSION

Acute toxicity - microorganisms EC₅₀, 3 hours: 28.52 mg/l, Activated sludge

DITHIO-2,2 BIS(BENZMETHYLAMIDE)

Toxicity Very toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Acute toxicity - fish LC₅₀, 96 hours: 0.8567 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 0.0289 mg/l, Daphnia magna

Acute toxicity - aquatic plants ErC₅₀, 72 hours: 0.401 mg/l, Pseudokirchneriella subcapitata

2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE

Toxicity Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Acute toxicity - fish LC₅₀, 96 hours: 0.24 mg/l, Oncorhynchus mykiss (Rainbow trout)
LC₅₀, 96 hours: 1.5 mg/l, Cyprinodon variegatus (Sheepshead minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 0.92 mg/l, Daphnia magna
LC₅₀, 48 hours: 0.48 mg/l, Marinewater invertebrates

Acute toxicity - aquatic plants ErC₅₀, 96 hours: 0.71 mg/l, Skeletonema costatum (marine diatom)
ErC₅₀, 7 days: 0.23 mg/l, Lemna gibba
ErC₅₀, 72 hours: 0.33 mg/l, Pseudokirchneriella subcapitata
OECD 201
NOEC, 72 hours: 0.068 mg/l, Pseudokirchneriella subcapitata
OECD 201

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOEC, 32 days: 0.16 mg/l, Pimephales promelas (Fat-head Minnow)

Chronic toxicity - aquatic invertebrates NOEC, 21 hours: 0.42 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

1,2-BENZISOTHAZOL-3(2H)-ONE

PRIMAL AC 261K ACRYLIC EMULSION

Persistence and degradability Not readily biodegradable.

Biodegradation - Degradation 24%: 28 days
OECD 301B

DITHIO-2,2 BIS(BENZMETHYLAMIDE)

Persistence and degradability The product is not expected to be biodegradable.

Biodegradation - Degradation <1%: 28 days

Chemical oxygen demand 690 mg/g

2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.

1,2-BENZISOTHIAZOL-3(2H)-ONE

Bioaccumulative potential Bioaccumulation is unlikely. BCF: 3.2, Fish Calculation method.

Partition coefficient log Pow: 1.17

DITHIO-2,2 BIS(BENZMETHYLAMIDE)

Bioaccumulative potential Bioaccumulation is unlikely. BCF: 32, Cyprinus carpio (Common carp)

Partition coefficient Pow: 2.73 Estimated value.

2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient log Pow: 1.4

12.4. Mobility in soil

Mobility Partly miscible.

Ecological information on ingredients.

1,2-BENZISOTHIAZOL-3(2H)-ONE

Mobility No information available.

DITHIO-2,2 BIS(BENZMETHYLAMIDE)

Mobility The product is insoluble in water.

2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE

PRIMAL AC 261K ACRYLIC EMULSION

Mobility No information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

1,2-BENZISOTHIAZOL-3(2H)-ONE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

DITHIO-2,2 BIS(BENZ METHYLAMIDE)

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects No information available.

Ecological information on ingredients.

1,2-BENZISOTHIAZOL-3(2H)-ONE

Other adverse effects The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

DITHIO-2,2 BIS(BENZ METHYLAMIDE)

Other adverse effects The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE

Other adverse effects The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Do not puncture or incinerate, even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

PRIMAL AC 261K ACRYLIC EMULSION

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

PRIMAL AC 261K ACRYLIC EMULSION

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
 CAS: Chemical Abstracts Service.
 DNEL: Derived No Effect Level.
 IATA: International Air Transport Association.
 IMDG: International Maritime Dangerous Goods.
 Kow: Octanol-water partition coefficient.
 LC₅₀: Lethal Concentration to 50 % of a test population.
 LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
 PBT: Persistent, Bioaccumulative and Toxic substance.
 PNEC: Predicted No Effect Concentration.
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
 RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
 vPvB: Very Persistent and Very Bioaccumulative.
 IARC: International Agency for Research on Cancer.
 MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.
 cATpE: Converted Acute Toxicity Point Estimate.
 BCF: Bioconcentration Factor.
 BOD: Biochemical Oxygen Demand.
 EC₅₀: 50% of maximal Effective Concentration.
 LOAEC: Lowest Observed Adverse Effect Concentration.
 LOAEL: Lowest Observed Adverse Effect Level.
 NOAEC: No Observed Adverse Effect Concentration.
 NOAEL: No Observed Adverse Effect Level.
 NOEC: No Observed Effect Concentration.
 LOEC: Lowest Observed Effect Concentration.
 DMEL: Derived Minimal Effect Level.
 EL50: Exposure Limit 50
 hPa: Hectopascal
 LL50: Lethal Loading fifty
 OECD: Organisation for Economic Co-operation and Development
 POW: Octanol-water partition coefficient
 SCBA: self-contained breathing apparatus
 STP: Sewage Treatment Plant
 VOC: Volatile Organic Compounds

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity
 Aquatic Acute = Hazardous to the aquatic environment (acute)
 Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Key literature references and sources for data

Supplier's information.

Classification procedures according to Regulation (EC) 1272/2008

EUH208: Calculation method. Not classified.: Calculation method.

Revision comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date

12/10/2022

PRIMAL AC 261K ACRYLIC EMULSION

Version number	2.000
Supersedes date	16/10/2020
SDS number	61021
SDS status	Approved.
Hazard statements in full	H301 Toxic if swallowed. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE, 2-METHYL-1,2-BENZOTHAZOL-3(2H)-ONE. May produce an allergic reaction.
Signature	Lisa Bland

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.