



SAFETY DATA SHEET

ACRYSOL RM 8W RHEOLOGY MODIFIER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ACRYSOL RM 8W RHEOLOGY MODIFIER

Product number 61041

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Surface coating Additive Rheology Modifier

1.3. Details of the supplier of the safety data sheet

Supplier Univar Solutions UK Ltd
Aquarius House
6 Mid Point Business Park
Bradford
BD3 7AY
+44 1274 267300
+44 1274 267306
SDS.EMEA@univarsolutions.com

1.4. Emergency telephone number

Emergency telephone SGS - +32 (0)3 575 55 55 (24h)

Sds No. 61041

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

ACRYSOL RM 8W RHEOLOGY MODIFIER

Precautionary statements

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P501 Dispose of contents/ container in accordance with local regulations.

Contains

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB. The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1) >= 0.0001 - < 0.005 %

CAS number: 55965-84-9

EC number: 611-341-5

REACH registration number: 01-2120764691-48-XXXX

M factor (Acute) = 100

M factor (Chronic) = 100

ATE: Acute Toxicity Estimate.Oral64mg/kg

ATE: Acute Toxicity Estimate.Dermal92.4mg/kg

ATE: Acute Toxicity Estimate.Inhalation0.171mg/l4hourDust/Mist

Skin Corr. 1C - H314

>= 0.6%

Skin Irrit. 2 - H315

0.06 - < 0.6 %

Eye Irrit. 2 - H319

0.06 - < 0.6 %

Skin Sens. 1A - H317

>= 0.0015 %

Eye Dam. 1 - H318

>= 0.6 %

Classification

Acute Tox. 3 - H301

Acute Tox. 2 - H310

Acute Tox. 2 - H330

Skin Corr. 1C - H314

Eye Dam. 1 - H318

Skin Sens. 1A - H317

Aquatic Acute 1 - H400

Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

ACRYSOL RM 8W RHEOLOGY MODIFIER

4.1. Description of first aid measures

General information	First aid personnel should wear appropriate protective equipment during any rescue. Wear protective clothing as described in Section 8 of this safety data sheet.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Wash clothing and clean shoes thoroughly before reuse. Get medical attention if any discomfort continues. Provide shower facilities near the workplace.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	May cause an allergic skin reaction.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	When heated and in case of fire, toxic vapours/gases may be formed.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of the following substances: Carbon.

5.3. Advice for firefighters

Protective actions during firefighting	No action shall be taken without appropriate training or involving any personal risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Do not use water jet as an extinguisher, as this will spread the fire. Contain and collect extinguishing water. Avoid the spillage or runoff entering drains, sewers or watercourses. Evacuate area.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes.
-----------------------------	---

6.2. Environmental precautions

ACRYSOL RM 8W RHEOLOGY MODIFIER

Environmental precautions Harmful to aquatic life with long lasting effects. Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if safe to do so. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Avoid spilling. Avoid release to the environment. Observe good chemical hygiene practices. Product residues retained in emptied containers can be hazardous.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Only store in correctly labelled containers. Store away from the following materials: Strong oxidising agents.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Ingredient comments No exposure limits known for ingredient(s).

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1) (CAS: 55965-84-9)

DNEL	Workers - Inhalation; Long term local effects: 0.02 mg/m ³
	Workers - Inhalation; Short term local effects: 0.04 mg/m ³
	Consumer - Inhalation; Long term local effects: 0.02 mg/m ³
	Consumer - Inhalation; Short term local effects: 0.04 mg/m ³
	Consumer - Oral; Long term systemic effects: 0.09 mg/kg/day
	Consumer - Oral; Short term systemic effects: 0.11 mg/kg/day
PNEC	Fresh water; 3.39 µg/l
	marine water; 3.39 µg/l
	STP; 0.23 mg/l
	Soil; 0.01 mg/kg/day
	Intermittent release; 3.39 µg/l
	Sediment (Freshwater); 0.027 mg/kg/day
	Sediment (Marinewater); 0.027 mg/kg/day

8.2. Exposure controls

ACRYSOL RM 8W RHEOLOGY MODIFIER

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The selected gloves should have a breakthrough time of at least 4 hours. Nitrile rubber. Polyvinyl chloride (PVC). Neoprene. Thickness: > 0.35 mm Do not use the following: Polyvinyl alcohol (PVA). To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Remove contaminated clothing and protective equipment before entering eating areas. Eye wash facilities and emergency shower must be available when handling this product.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. If ventilation is inadequate, suitable respiratory protection must be worn. Organic vapour filter. Combination filter, type A2/P2. EN 136/140/141/145/143/149

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless. to Yellow. Clear. to Hazy
Odour	Mild.
Odour threshold	No information available.
pH	pH (concentrated solution): 4.0 - 8.0
Melting point	0°C Water
Pour Point	No information available.
Freezing Point	No information available.
Initial boiling point and range	100.00°C @ 760 mm Hg Water
Flash point	The product is non-combustible.
Evaporation rate	< 1.00 (butyl acetate = 1) Water
Evaporation factor	No information available.
Flammability (solid, gas)	Not applicable.

ACRYSOL RM 8W RHEOLOGY MODIFIER

Upper/lower flammability or explosive limits	Not applicable.
Other flammability	No information available.
Vapour pressure	2266.4808000 Pa @ 20°C Water
Vapour density	< 1.0000 Water
Relative density	1.0000 - 1.2000
Bulk density	No information available.
Solubility(ies)	Soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	Not applicable.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Explosive under the influence of a flame	No information available.
Oxidising properties	No information available.

9.2. Other information

Refractive index	No information available.
Particle size	No information available.
Molecular weight	No information available.
Volatility	78 - 80 % Water
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not polymerise. The following materials may react with the product: Strong oxidising agents.
------------------------------------	---

10.4. Conditions to avoid

Conditions to avoid	None known.
---------------------	-------------

10.5. Incompatible materials

Materials to avoid	Strong oxidising agents.
--------------------	--------------------------

10.6. Hazardous decomposition products

ACRYSOL RM 8W RHEOLOGY MODIFIER

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of the following substances: Carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) This product has low toxicity. This information is based on test data from similar products LD₅₀ > 5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) This information is based on test data from similar products LD₅₀ > 2000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined.

Skin corrosion/irritation

Skin corrosion/irritation This information is based on test data from similar products May be slightly irritating to skin. Redness.

Serious eye damage/irritation

Serious eye damage/irritation This information is based on test data from similar products May be slightly irritating to eyes.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro This information is based on test data from similar products Negative.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - fertility No information available.

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Toxicokinetics

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Inhalation

Gas or vapour in high concentrations may irritate the respiratory system.

Ingestion

May cause discomfort if swallowed.

Skin contact

May be slightly irritating to skin. Redness. May cause an allergic skin reaction.

Eye contact

May cause temporary eye irritation.

ACRYSOL RM 8W RHEOLOGY MODIFIER

Toxicological information on ingredients.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)

Acute toxicity - oral

Acute toxicity oral (LD ₅₀ mg/kg)	64.0
Species	Rat
Notes (oral LD ₅₀)	LD ₅₀ 64 mg/kg, Oral, Rat Toxic if swallowed.
ATE oral (mg/kg)	64.0

Acute toxicity - dermal

Acute toxicity dermal (LD ₅₀ mg/kg)	92.4
Species	Rabbit
Notes (dermal LD ₅₀)	LD ₅₀ 92.4 mg/kg, Dermal, Rabbit Fatal in contact with skin.
ATE dermal (mg/kg)	92.4

Acute toxicity - inhalation

Acute toxicity inhalation (LC ₅₀ dust/mist mg/l)	0.171
Species	Rat
Notes (inhalation LC ₅₀)	LC ₅₀ 0.171 mg/l, 4 hours, Dust/Mist Rat Fatal if inhaled.
ATE inhalation (dusts/mists mg/l)	0.171

Skin corrosion/irritation

Skin corrosion/irritation	Causes severe burns. Rabbit OECD 404
---------------------------	--------------------------------------

Serious eye damage/irritation

Serious eye damage/irritation	Causes serious eye damage. May cause permanent damage if eye is not immediately irrigated. May cause chemical eye burns. Rabbit
-------------------------------	---

Respiratory sensitisation

Respiratory sensitisation	No information available.
---------------------------	---------------------------

Skin sensitisation

Skin sensitisation	May cause an allergic skin reaction. Guinea pig maximization test (GPMT) - Guinea pig: Sensitising. OECD 406
--------------------	--

Germ cell mutagenicity

Genotoxicity - in vitro	Inconclusive data.
Genotoxicity - in vivo	Chromosome aberration: Negative. Rat Chromosome aberration: Negative. Mouse Micronucleus assay: Negative. Rat

Carcinogenicity

Carcinogenicity	No evidence of carcinogenicity in animal studies.
-----------------	---

ACRYSOL RM 8W RHEOLOGY MODIFIER

Reproductive toxicity

Reproductive toxicity - fertility Fertility - NOAEL 16.3 - 24.7 mg/kg, Oral, Rat P Fertility - NOAEL (90d) 16.3 - 24.7 mg/kg, Oral, Rat F1 Fertility, Two-generation study - NOAEL (P) 2.8 - 4.4, (F1) 22.7 - 28, (F2) 35.7 - 39.1 mg/kg, Oral, Rat

Reproductive toxicity - development Based on available data the classification criteria are not met. Developmental toxicity: - NOAEL: 15 mg/kg, Oral, Rat Maternal toxicity: - NOAEL: <= 3.95 mg/kg, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure. NOAEL (90 d) 16.3 - 24.7 mg/kg, Oral, Rat NOAEL (91 d) <=0.104 mg/kg, Dermal, Rat NOAEL (91 d) 0.00034 mg/l, Inhalation, Rat

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Toxicokinetics The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Inhalation Fatal if inhaled.

Ingestion Toxic if swallowed.

Skin contact Fatal in contact with skin. Causes severe burns. May cause an allergic skin reaction.

Eye contact Causes serious eye damage. May cause permanent damage if eye is not immediately irrigated. May cause chemical eye burns.

SECTION 12: Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)

Ecotoxicity Very toxic to aquatic life with long lasting effects.

12.1. Toxicity

Toxicity Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)

Toxicity Very toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

ACRYSOL RM 8W RHEOLOGY MODIFIER

LE(C)₅₀	0.001 < L(E)C ₅₀ ≤ 0.01
M factor (Acute)	100
Acute toxicity - fish	EC ₅₀ , 96 hours: 0.22 mg/l, Oncorhynchus mykiss (Rainbow trout) OECD 203
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 0.1 mg/l, Daphnia magna OECD 202
Acute toxicity - aquatic plants	EC ₅₀ , 48 hours: 0.0052 mg/l, Skeletonema costatum (marine diatom) OECD 201 NOEC, 48 hour: 0.00049 mg/l, Skeletonema costatum (marine diatom) OECD 201
Acute toxicity - microorganisms	EC ₅₀ , 3 hour: 7.92 mg/l, Activated sludge OECD 209
<u>Chronic aquatic toxicity</u>	
M factor (Chronic)	100
Chronic toxicity - fish early life stage	NOEC, 28 days: 0.098 mg/l, Oncorhynchus mykiss (Rainbow trout) OCED 215
Chronic toxicity - aquatic invertebrates	NOEC, 21 day: 0.004 mg/l, Daphnia magna OECD 202

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)

Persistence and degradability	The product is readily biodegradable.
Biodegradation	- >60%: 28 days OECD 301D

12.3. Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Partition coefficient	No information available.

Ecological information on ingredients.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)

Bioaccumulative potential	BCF: 3.6,
Partition coefficient	log Pow: -0.71 - 0.75 OECD 107

12.4. Mobility in soil

Mobility	Soluble in water.
-----------------	-------------------

Ecological information on ingredients.

ACRYSOL RM 8W RHEOLOGY MODIFIER

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)

Mobility No information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Ecological information on ingredients.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] & 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)

Other adverse effects The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Do not puncture or incinerate, even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

ACRYSOL RM 8W RHEOLOGY MODIFIER

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
COMMISSION REGULATION (EU) 2020/878 of 18 June 2020

Restrictions (Annex XVII Regulation 1907/2006)

CAUTION - Chemical may be subject to REACH RESTRICTIONS - see Annex XVII. This product is/contains a substance that is included in REGULATION (EC) No 1907/2006 (REACH) ANNEX XVII - RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES. Entry number: 3

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

ACRYSOL RM 8W RHEOLOGY MODIFIER

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
 CAS: Chemical Abstracts Service.
 DNEL: Derived No Effect Level.
 IATA: International Air Transport Association.
 IMDG: International Maritime Dangerous Goods.
 Kow: Octanol-water partition coefficient.
 LC₅₀: Lethal Concentration to 50 % of a test population.
 LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
 PBT: Persistent, Bioaccumulative and Toxic substance.
 PNEC: Predicted No Effect Concentration.
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
 RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
 vPvB: Very Persistent and Very Bioaccumulative.
 IARC: International Agency for Research on Cancer.
 MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.
 cATpE: Converted Acute Toxicity Point Estimate.
 BCF: Bioconcentration Factor.
 BOD: Biochemical Oxygen Demand.
 EC₅₀: 50% of maximal Effective Concentration.
 LOAEC: Lowest Observed Adverse Effect Concentration.
 LOAEL: Lowest Observed Adverse Effect Level.
 NOAEC: No Observed Adverse Effect Concentration.
 NOAEL: No Observed Adverse Effect Level.
 NOEC: No Observed Effect Concentration.
 LOEC: Lowest Observed Effect Concentration.
 DMEL: Derived Minimal Effect Level.
 EL50: Exposure Limit 50
 hPa: Hectopascal
 LL50: Lethal Loading fifty
 OECD: Organisation for Economic Co-operation and Development
 POW: Octanol-water partition coefficient
 SCBA: self-contained breathing apparatus
 STP: Sewage Treatment Plant
 VOC: Volatile Organic Compounds

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity
 Aquatic Acute = Hazardous to the aquatic environment (acute)
 Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Key literature references and sources for data

Supplier's information.

Classification procedures according to Regulation (EC) 1272/2008

Skin Sens. 1 - H317: Calculation method. Aquatic Chronic 3 - H412: Calculation method.

Revision comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date

28/12/2022

ACRYSOL RM 8W RHEOLOGY MODIFIER

Version number	3.000
Supersedes date	24/02/2022
SDS number	61041
SDS status	Approved.
Hazard statements in full	H301 Toxic if swallowed. H310 Fatal in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H330 Fatal if inhaled. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
Signature	Lisa Bland

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.